



Lackland AFB Commissary, TX Sustainment Project Proposed Ammonia/CO2 Refrigeration System Analysis











Presenter:

Rob Arthur, P.E.
LEED AP BD+C
CTA Architects and Engineers
Principal/Director of Refrigeration Engineering











Disclaimer:

Defense Commissary Agency (DeCA)

DeCA has no political agenda as it relates to environmental concerns or energy usage.

DeCA is committed to best business practices and is looking for ways to control capital and operating costs in the future and meet the energy and sustainability goals the U.S. Government has established for all public buildings.





Introductions





Agenda

- Project Summary
- Goals
- Ammonia Plume Study Findings
- Energy Model Results
- Life Cycle Analysis
- Question and Answer











Project Summary

- •Existing 117,000 Sq/Ft Commissary in San Antonio, TX
- Sustainment Project
- Project Design Partners
 - DeCA
 - •EPA
 - NREL (DOE/Commercial Building Partnership)
 - Design Consultants









June 12-13 2012 | Washington DC



















Goals of Project

- •Low Global Warming Potential (GWP) System or 100% Natural Refrigerant
- More Energy Efficient then Industry Standard Systems
- •Eliminate Safety concerns
- Serviceable Equipment
- Reasonable Costs

Current Readily Available Systems

- Low Global Warming Potential (GWP) System
- Less Energy Efficient then Industry Standard Systems

Possible Systems that meet Goals

- •Sub Critical/Transcritical CO2 Systems
- Ammonia/CO2 Cascade System























Implemented System Example

- · Modular design with integrated condenser-water pump-station and manifolding
- Total capacity of 1,260 kBtu/Hr for MT and LT operation
- · Paneled enclosure for outdoor installation



REFRIGERATION SYSTEMS


















Building Model





Why Consider Ammonia/CO2 System

- State and National Codes and EPA or Legislative Regulations
 - Energy Code Requirements
 - Penalties for Leaks of HFC's
 - Possible Taxes on HFC's (R-404a)
 - Possible HFC Refrigerant Charge Limits
 - Prevent need for future Refrigerant Conversion











Why Consider Ammonia/CO2 System

- Environmental Concerns
 - Industry Standard Traditional Refrigeration Systems
 - •On average grocery stores leak 1000 lbs of refrigerant a year
 - •25% leak rate
 - Advanced Refrigeration Systems
 - •Minimal to no leaks of Synthetic Refrigerants











Why Consider Ammonia/CO2 System

- Energy Consumption
 - Expect 8% Energy Savings on this project
 - •Other countries with more experience claiming 25% or higher Energy Savings









Ammonia Plume Study

What did the Study Seek to do?

- Determine if ammonia was safe for this installation?
- Can the proposed system impact the surrounding area?
- Is there risk for the surrounding population?
- Determine most likely and worst case impacts.











Ammonia Plume Study

So What Does All This Mean?

- The results of this study suggest that in the vast majority of failure scenarios, there would be very little potential for public health risks associated with the proposed facility.
- The results of the dense gas modeling suggest that there is some small potential for public impacts during catastrophic worst case scenarios. However, in the case of small leaks or non-catastrophic events, the system poses little health based threats, with most impacts being limited to short lived unpleasant odors.
- The ammonia in the system is continuously monitored for leaks. Should a leak of sufficient size be detected, you will be notified of the event.









Energy Model

- Energy Monitoring
 - •Over 1 year of existing energy monitoring prior to project
 - Continuous energy monitoring after project
- Energy Consumption
 - Expect 8% Energy Savings on compressor system over baseline
 - Direct Expansion Ammonia system is not most efficient option
 - •Other countries with more experience claiming 25%+ Energy Savings









System		Baseline System	Proposed Sy	
	Subsystem	4-Rack R-404A System	Cascade NH3 Over CO2 System	
	LT Compressors	170,67		
	MT Compressors			
Rack	Primary Compressors		277,369	
Systems	Secondary Compressors		81,105	
	Secondary Pumps		6,531	
	SubT Rack Systems	396,390	365,005	
	Energy Use Compared To Existing System		7.9% Less	











System	Subsystem	Baseline System	Proposed S	
		4-Rack R-404A System	Cascade NH3 Over CO2 System	
LT End Uses	Fans, Lights, ASW, Defrost	323,084	323,084	
MT End Uses	Fans, Lights, ASW, Defrost	186,525	186,525	
Rack Systems	LT Compressors	170,671		
	MT Compressors	225,719		
	Primary Compressors		277,369	
	Secondary Compressors		81,105	
	Secondary Pumps		6,531	
Condensers	Condenser Fans	193,541	194,855	

SubT End-Uses	509,609	509,609
Juni Liiu-0363	309,009	303,003
SubT Rack Systems	396,390	365,005
SubT Condensing Systems	193,541	194,855
Just Condensing Systems	155,541	154,055
Total System Loads	1,099,540	1,069,469

Energy Use Compared To	2.7% Less
Existing System	2.7 % Less











	R-404A Industry Std	Ammonia/CO2	
Life of equipment (yrs)	20	20	
Discount Rate for non energy related factors	0.06	0.06	
JPV Factor for Annual Energy Costs	14.81	14.81	
Total First Cost		28%	
Annual Energy cost as Uniform Present Value		-3%	
Annual Refrigerant cost as Uniform Present Value		-93%	
Annual Maintenance cost as Uniform Present Value		-39%	
Total 20 Year Life Cycle Cost as Uniform Present Value			340,175.99









Question Answer

Thank you!





