



ATMO
sphere

Applying Low Charge Ammonia Systems To An Operating Dairy

Kurt Liebendorfer
Vice President – Evapcold



Taneytown, Maryland



The facility is an operating process plant that has an outdated existing ammonia system & the plant is undergoing a significant expansion. Safe operation & minimizing impact to production is a key priority



- The Memphis, TN plant produces a variety of beverages, including a complete line of milks and juices.
- Expansion & remodeling project includes expanded production, equipment upgrades, new packaging line and an addition to its refrigerated warehouse.



| EVAPCOLD Model | Total TR | Total lbs. NH ₃ |
|-------------------------------------|------------|----------------------------|
| 35°F Coolers: (2) LCR-090P-M25-2H-W | 200 | 764 |
| Process: (2) LCR-130C-M20-2831-N-W | 260 | 260 |
| | 460 | 964 |
| | | (2.1 lb/TR) |

Penthouse Units
Chillers




Existing NH3 system = 9,000 lbs.

Expansion would put them over 10,000 lb. TQ



Significantly reducing the quantity of ammonia to 1/10 the charge - including the expansion. Allowing for safer operation, a real reduction of the regulatory burden and a lower cost of ownership for the owner

- Cooling to new warehouse & to exiting plant via ducted supply air to separate rooms.
- Eliminates the need to mount the rooftop units on the existing roof structure.
- Eliminates running ammonia piping thru new & existing plant.



Plug & Play:

- Modular sections make it fast & easy to install in ONE DAY!
- Refrigeration work is substantially complete @ same time as steel erection milestone





Easier Site Coordination & Less Impact On Plant Operations:

- Refrigeration field work is significantly reduced inside the existing operating plant & the plant jobsite
- Less disruptive to plant production
- Faster project installation
- Faster startup
- Safer system operation
- Operating Dock to the left will be temporarily shut down while next new steel bay is erected and 2nd Evapcold unit is quickly installed



EVAPCO GUARANTEED PERFORMANCE



Penthouse Units



Chillers

| | | |
|------------------------------|-------------------|---------|
| MODEL NUMBER | LCR-090P-M25-2H-A | |
| Unit Qty. | 2 | |
| Unit Tag | Milk Cooler | |
| LCR DESIGN CONDITIONS | | |
| Total Cooling Capacity, Tons | 100 | |
| Room Temp DB, °F | 34 | |
| Outdoor Temp DB, °F | 95 | |
| Outdoor Temp WB, °F | 78 | |
| Airflow, CFM | 91,484 | |
| Comp. Sat. Suct. Temp | 20 | |
| Comp. Sat. Disch. Temp. | 112 | 106 |
| Compressor Rpm | 3829.57 | 3708.58 |
| Shaft BHP, HP | 160.20 | 143.79 |
| BHP/Ton at Design Conditions | 1.6 | 1.4 |
| Capacity Control Type | Modulated w/ VFD | |

| | | |
|----------------------------------|-----------------------|--|
| MODEL NUMBER | LCR-130C-M20-2634-N-W | |
| CHILLER DESIGN CONDITIONS | | |
| Total Cooling Capacity, Tons | 130 | |
| Outdoor Temp DB, °F | 95 | |
| Temp WB, °F | 78 | |
| Chilled Fluid | | |
| Fluid Type | Propylene Glycol | |
| Fluid Solution Percent, % | 35 | |
| Return Chilled Fluid Temp, °F | 34 | |
| Supply Chilled Fluid Temp, °F | 26 | |
| Chilled Fluid Flow Rate, Gpm | 421.6 | |
| Comp. Sat. Suct. Temp. Comp. | 20 | |
| Sat. Disch. Temp. Compressor | 98 | |
| Rpm | 3639 | |
| Shaft BHP, HP | 151.6 | |
| BHP/Ton at Design Conditions | 1.17 | |

Factory Packaged Low Charge Ammonia - Distributed Refrigeration Systems -



- 1. Significantly Less Ammonia Charge***
- 2. Significantly Lower Regulatory Burden***
- 3. Lower Energy***
- 4. Eliminate Central Machine Room***
- 5. Faster Installation & Startup***
- 6. Competitive Cost***
- 7. Reduce Tax Burden***
- 8. Lower Life Cycle Costs***
- 9. Latest Technology***
- 10. Comprehensive Documentation***





ATMO
sphere

Thank you very much!

